| | Тур | Hi ts | Search Text | DBs | Time Stamp | m m e | r D e f i | Errors |
|---|-----|----------|---|--|---------------------|--|--|--------|
| 1 | BRS | 20 38 | mems with sensor | USPAT; US-PGPUB; EPO; JPO; DERWENT; | 2004/05/19 23:33 | | | 0 |
| 2 | BRS | 15 9 | mems with sensor and sensor with stress\$6 | 世 8坪 A平身B US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/18 14:56 | | ************************************** | 0 |
| 3 | BRS | 0 | mems with sensor and sensor with stress\$6 and sensor with silicon with amorphous | | 2004/05/06 15:17 | 11 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 | | 0 |
| 4 | BRS | 83 | mems with sensor and sensor with stress\$6 and sensor with silicon | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/06 15:22 | | | 0 |
| 5 | BRS | 21 | mems with sensor and flexible with conduct\$7 with substrate | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/06 15:30 | ATTENDED TO THE PROPERTY OF TH | | 0 |
| 6 | BRS | 1 | mems with sensor and sensor with stress\$6 and molybdenum with chromium | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/07 19:42 | | | 0 |
| 7 | BRS | 43 | mems with sensor and sensor with stress\$6 and deformat\$6 | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/07 19:43 | | | 0 |
| 8 | BRS | 3 | mems with sensor and sensor with stress\$6 and deformat\$6 with electrode | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/07 19:44 | | | 0 |

05/20/2004, EAST Version: 1.4.1

| | Туре | Hi ts | Search Text | DBs | Time Stamp | Comments | r D e f i | Error |
|----|----------|----------|---|--|---------------------|----------|-----------------------|-------|
| 9 | BRS | 0 | mems with sensor and sensor with stress\$6 and mim near capacitor | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/07 19:49 | | | 0 |
| 10 | BRS | 3 | mems with sensor and mim near capacitor | JPO; DERWENT; | 2004/05/07 20:03 | | | 0 |
| 11 | IS& R | 2 | ("5848685").PN | 世 号毕 五甲 D B US-PGPUB; EPO; JPO; DERWENT; | 2004/05/07 20:03 | | | 0 |
| 12 | BRS | 19 | 5848685.URPN. | IBM TDB USP A T | 2004/05/07 20:04 | | | 0 |
| 13 | BRS | 13 | ("3842189" "3952404" "4189342" "5613861" "5665648" "5848685" "5914218" "5944537" "5979892" "6184065" "6184699" "6213789" "6290510").PN. | USPAT | 2004/05/07 20:11 | | | 0 |
| 14 | BRS | 9 | mems and sensor with coat\$6 with conduct\$6 and | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/18 15:02 | | | 0 |
| 15 | BRS | 7 | <u>i</u> | USPAT; US-PGPUB; EPO; JPO; DERWENT; | 2004/05/18 15:04 | | | 0 |
| 16 | BRS | 3 | ଲଞ୍ଜିଞ୍ ^ଞ គ្រឹង sensor with releas\$6 with | 世島神五甲身B US-PGPUB; EPO; JPO; DERWENT; | 2004/05/18 15:09 | | | 0 |
| 17 | BRS | 1 | memesend | 世島神A平DB US-PGPUB; EPO; JPO; DERWENT; IBM TDB | 2004/05/18 | | | 0 |

| | Тур | Hi ts | Search Text | DBs | Time Stamp | m e n | r D e f i | o r s |
|----|-----|----------|--|--|---------------------|--|--|-------------|
| 18 | BRS | 78 6 | mems with sensor and (releas\$6 or spring) with (releas\$6 or deform\$6) | | 2004/05/18 15:12 | deleted the majorite service reverse refers reverse transcent and the design to the design of the de | | 0 |
| 19 | BRS | 23 4 | mems and sensor with coat\$6 and (releas\$6 or spring) with (releas\$6 or | | 2004/05/18 15:13 | | *************************************** | 0 |
| 20 | BRS | 28 | memsrana) sensor with coat\$6 with (conduct\$6 or metal) and (releas\$6 or spring) with (releas\$6 or | i | 2004/05/18 16:10 | | | 0 |
| 21 | BRS | 0 | deform\$6) sensor with coat\$6 with (conduct\$6 or metal) and mems with (releas\$6 or spring or deform\$6) | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/18 16:11 | 11. Den 11. 11. 11. 11. 11. 11. 11. 11. 11. 11 | 110 of the little with the little state of the | 0 |
| 22 | BRS | 62 | sensor with (conduct\$6 or metal) and mems with (releas\$6 or spring or deform\$6) | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/18 16:28 | | | 0 |
| 23 | BRS | 55 3 | mems and sensor with (releas\$6 or spring or deform\$6) | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/18 16:29 | | | 0 |

| | Тур | Hi ts | Search Text | DBs | Time Stamp | m m e | r D e f | Errors |
|----|----------|----------|--|---|---------------------|-------------|---------|--------|
| 24 | BRS | 92 | mems with sensor with (releas\$6 or spring or deform\$6) | i e | 2004/05/18 16:29 | | | 0 |
| 25 | BRS | 27 | mems with sensor with (releas\$6 or spring or deform\$6) and sensor with (metal or conduct\$6) | 1 | 2004/05/18 16:32 | | | 0 |
| 26 | BRS | 2 | mems and release near (layer or film) and sensor with spring and sensor with (metal or | I . | 2004/05/18 16:36 | | | 0 |
| 27 | BRS | 7 | memsuct§6) release near (layer or film) and sensor with | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 13:20 | | | 0 |
| 28 | IS& R | 1 | spring ("6734425").PN | USPAT; US-PGPUB; EPO; JPO; DERWENT; | 2004/05/19 23:23 | | | 0 |
| 29 | IS& R | 2 | ("6396677").PN | 世 8坪A 平 D B US-PGPUB; EPO; JPO; DERWENT; | 2004/05/19 23:23 | | | 0 |
| 30 | BRS | 57 9 | mems with sensor and spring | 世島姓 名早身B US-PGPUB; EPO; JPO; DERWENT; | 2004/05/19 23:33 | | | 0 |
| 31 | BRS | 54 | mems with sensor and spring and gallium adj arsenide | IBM TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:34 | | | 0 |

| | Тур | Hi ts | Search Text | DBs | Time Stamp | m m e | e f i n | r |
|----|-----|----------|--|--|---------------------|-------------|------------------|---|
| 32 | BRS | 4 | mems with sensor and spring and gallium adj arsenide and amorphous adj silicon | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:35 | | | 0 |
| 33 | BRS | 16 | amorphous adj | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:35 | | | 0 |
| 34 | BRS | 0 | memscand sensor and spring and gallium adj arsenide and hydrogen\$6 with amorphous | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:36 | | | 0 |
| 35 | BRS | 20 | memssandcon sensor and hydrogen\$6 with amorphous | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:36 | | | 0 |
| 36 | BRS | 0 | . ~ | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:37 | | | 0 |
| 37 | BRS | 2 | Menssähicon sensor same hydrogen\$6 with amorphous | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:40 | | | 0 |
| 38 | BRS | 0 | menssähäcon sensor near gallium adj | USPAT; US-PGPUB; EPO; JPO; DERWENT; | 2004/05/19 23:40 | | | 0 |
| 39 | BRS | 0 | memenade sensor near3 gallium adj | 世島姓為罕身B US-PGPUB; EPO; JPO; DERWENT; | 2004/05/19 23:40 | | | 0 |
| 40 | BRS | 16 | memsnäde sensor with gallium adj arsenide | 世島姓 <u>A</u> 罕身B US-PGPUB; EPO; JPO; DERWENT; IBM TDB | 2004/05/19 23:49 | | | 0 |

| | Тур | ts | Search Text | DBs | Time Stamp | m m e n t | ErrorDefinitio | rrors |
|----|-----|----|---------------------------------------|--|---------------------|-----------|----------------|-------|
| 41 | BRS | | mems and sensor with laser with | USPAT; US-PGPUB; EPO; JPO; DERWENT; | 2004/05/19 23:50 | | | 0 |
| 42 | BRS | 8 | laser with array with | ₩₩₩₩₩₩ US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:53 | | | 0 |
| 43 | BRS | | sensor and laser with | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/05/19 23:54 | | | 0 |